



Uzina Mecanică Cugir SA

515600, Cugir, Alba, Romania, 21 December 1989 Street, No.1,
Tel.: 0040 258 751 991, Fax: 0040 258 754 940
e-mail: office@umcugir.ro, officefps@umcugir.ro, umcugir@yahoo.com
www.umcugir.ro



Cal. 23 mm x 115 mm AIR TO AIR CANNON



I USE: The two-barrel cal. 23 x 115 mm air to air cannon is designed to be mounted on aircraft fighter. It is intended for air defense and against ground targets.

II ESSENTIAL DATA

- caliber:	23 mm
- rate of fire (normal conditions):	3000÷3400 rds/min
- velocity:	715 ±15 m/s
- mass:	
cal. 23 x 115mm Cannon	49.2 kg
cal. 23 x 115 mm Cannon with localizers	50 kg
- overall dimensions:	
- length	
cal. 23 x 115mm Cannon	1387 mm
cal. 23 x 115 mm Cannon with localizers	1537 mm
- breadth	165 mm
- height	168 mm
- barrel length:	1000 mm
- number of threads:	10
- threads pitch:	575 mm
- threads breadth:	4.8 mm
- barrel inner diameter:	
- on gaps	23.7 ^{+0.1} mm
- on full	23 ^{+0.1} mm
- triggering:	electric
- cocking:	manual cocking pyro-cartridge
- guaranteed number of rounds: to be fired (with the use of the pertaining set of spare parts):	maximum 4000 rounds/min (to this number there are allowed maximum 200 pyrotechnic cockings from which 80 without ammunition)

III PACKING

One air to air cannon is packed in a wooden box.	
Wooden box dimensions (Llxhx):	1673 x 345 x 319 mm
Net/Gross weight:	58,5/81,5 kg